



MIKO ENERGY



HYDRAULIC MODULE

Heating / Cooling / Hot water



TECHNICAL SPECS

MODEL	HU-3K/6L	HU-9K/6L
Power Supply(V/PH/Hz)	220~240/1/50	380~415/3/50
Ambient Temperature(°C)	-25~45	-25~45
Rated Flow(m³/h)	2.5	2.5
Electric Heating(kW)	3	3/6/9
Water Pressure Difference(kPa)	10	10
Water Pressure Range(MPa)	0.1~0.3	0.1~0.3
Noise(dB(A))	35	35
Net Dimensions(mm)	420/261/669	420/261/669
Packaging Dimensions(mm)	480/341/770	480/341/770
Net Weight(kg)	34	34
Gross Weight(kg)	37	37
Expansion Tank	6	
Range Extender Pump	Built - in	
Three-way Valve	Built - in	
Heat Pump Inlet/Outlet(in)	G1 external thread	
Water Tank Inlet/Outlet(in)	G1 external thread	
Heating Inlet/Outlet(in)	G1 internal thread	

* Please refer to the latest product manual for updated parameters

- **Wide operation range**
- **Wifi control, user friendly**
- **Efficient IOT management platform**
- **Portable and standard installation**
- **Remote monitoring, easy adjustment**
- **Space saving, integerated into a module**

